



IMS Question and Test Interoperability XML Binding

Version 2.0 Final Specification

Date Issued: 24 January 2005

IPR and Distribution Notices

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the specification set forth in this document, and to provide supporting documentation.

IMS takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on IMS's procedures with respect to rights in IMS specifications can be found at the IMS Intellectual Property Rights web page:

http://www.imsglobal.org/ipr/imsipr_policyFinal.pdf.

Copyright © 2005 IMS Global Learning Consortium. All Rights Reserved.

If you wish to copy or distribute this document, you must complete a valid Registered User license registration with IMS and receive an email from IMS granting the license to distribute the specification. To register, follow the instructions on the IMS website:

<http://www.imsglobal.org/specificationdownload.cfm>.

This document may be copied and furnished to others by Registered Users who have registered on the IMS website provided that the above copyright notice and this paragraph are included on all such copies. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to IMS, except as needed for the purpose of developing IMS specifications, under the auspices of a chartered IMS project group.

Use of this specification to develop products or services is governed by the license with IMS found on the IMS website:

<http://www.imsglobal.org/license.html>.

The limited permissions granted above are perpetual and will not be revoked by IMS or its successors or assigns.

THIS SPECIFICATION IS BEING OFFERED WITHOUT ANY WARRANTY WHATSOEVER, AND IN PARTICULAR, ANY WARRANTY OF NONINFRINGEMENT IS EXPRESSLY DISCLAIMED. ANY USE OF THIS SPECIFICATION SHALL BE MADE ENTIRELY AT THE IMPLEMENTER'S OWN RISK, AND NEITHER THE CONSORTIUM, NOR ANY OF ITS MEMBERS OR SUBMITTERS, SHALL HAVE ANY LIABILITY WHATSOEVER TO ANY IMPLEMENTER OR THIRD PARTY FOR ANY DAMAGES OF ANY NATURE WHATSOEVER, DIRECTLY OR INDIRECTLY, ARISING FROM THE USE OF THIS SPECIFICATION.

Copyright © 2005 by IMS Global Learning Consortium, Inc.
All Rights Reserved.

The IMS Logo is a registered trademark of IMS/GLC.

Document Name: IMS Question and Test Interoperability XML Binding

Date: 24 January 2005

Table of Contents

1.	INTRODUCTION	8
1.1	REFERENCES.....	8
2.	BINDING OF COMPLEX TYPES.....	9
3.	BINDING OF SIMPLE TYPES.....	10
4.	XML BINDING REFERENCE.....	11
4.1	<A>	11
4.2	<ABBR>	11
4.3	<ACRONYM>.....	12
4.4	<ADAPTIVE>	12
4.5	<ADDRESS>	12
4.6	<AND>.....	13
4.7	<ANYN>.....	13
4.8	<AREAMAPENTRY>	13
4.9	<AREAMAPPING>	13
4.10	<ASSESSMENTITEM>.....	14
4.11	ASSOCIABLECHOICE.ELEMENTGROUP	14
4.12	<ASSOCIABLEHOTSPOT>.....	14
4.13	<ASSOCIATEINTERACTION>	15
4.14	ATOMICBLOCK.ELEMENTGROUP	15
4.15	ATOMICINLINE.ELEMENTGROUP.....	16
4.16	16
4.17	<BANKPROFILE>.....	16
4.18	BASETYPE.TYPE.....	17
4.19	<BASEVALUE>.....	17
4.20	<BIG>	17
4.21	BLOCK.ELEMENTGROUP	18
4.22	BLOCKINTERACTION.ELEMENTGROUP	18
4.23	BLOCKSTATIC.ELEMENTGROUP	18
4.24	<BLOCKQUOTE>	18
4.25	BODYELEMENT.ELEMENTGROUP.....	19
4.26	BOOLEAN.TYPE.....	19
4.27	 	19
4.28	<CAPTION>	20
4.29	CARDINALITY.TYPE.....	20
4.30	<CATEGORIZEDSTATISTIC>	20
4.31	CHOICE.ELEMENTGROUP	21
4.32	<CHOICEINTERACTION>.....	21
4.33	<CITE>	21
4.34	<CODE>	22
4.35	<COL>	22
4.36	<COLGROUP>.....	22
4.37	<COMPOSITE>.....	23
4.38	<CONTAINS>	23
4.39	<CONTENTPROFILE>	23
4.40	COORDS.TYPE.....	24
4.41	<CORRECT>.....	24
4.42	<CORRECTRESPONSE>.....	24

4.43	<CUSTOMINTERACTION>.....	24
4.44	<CUSTOMOPERATOR>.....	25
4.45	DATE.TYPE	25
4.46	<DD>.....	25
4.47	<DEFAULT>	26
4.48	<DEFAULTVALUE>.....	26
4.49	<DELETE>	26
4.50	<DFN>	26
4.51	<DIV>	27
4.52	<DIVIDE>.....	27
4.53	<DL>	28
4.54	DLEMENT.ELEMENTGROUP.....	28
4.55	<DRAWINGINTERACTION>	28
4.56	<DT>	29
4.57	<DURATIONGTE>.....	29
4.58	<DURATIONLT>.....	29
4.59		29
4.60	<ENDATTEMPTINTERACTION>.....	30
4.61	<EQUAL>.....	30
4.62	<EQUALROUNDED>	31
4.63	<EXITRESPONSE>	31
4.64	<EXITTEMPLATE>	31
4.65	EXPRESSION.ELEMENTGROUP	31
4.66	<EXTENDEDTEXTINTERACTION>	32
4.67	<FEEDBACKBLOCK>.....	33
4.68	FEEDBACKELEMENT.ELEMENTGROUP	33
4.69	<FEEDBACKINLINE>	34
4.70	<FEEDBACKINTEGRATED>	34
4.71	<FEEDBACKMODAL>.....	34
4.72	<FEEDBACKTYPE>	34
4.73	FEEDBACKTYPE.TYPE.....	35
4.74	<FIELDVALUE>	35
4.75	FLOAT.TYPE	35
4.76	FLOW.ELEMENTGROUP	35
4.77	FLOWSTATIC.ELEMENTGROUP	36
4.78	<GAP>	36
4.79	GAPCHOICE.ELEMENTGROUP.....	36
4.80	<GAPIMG>.....	36
4.81	<GAPMATCHINTERACTION>	37
4.82	<GAPTEXT>	37
4.83	<GRAPHICASSOCIATEINTERACTION>	38
4.84	<GRAPHICGAPMATCHINTERACTION>	38
4.85	GRAPHICINTERACTION.ELEMENTGROUP	39
4.86	<GRAPHICORDERINTERACTION>	39
4.87	<GT>	39
4.88	<GTE>.....	40
4.89	<H1>	40
4.90	<H2>	40
4.91	<H3>	41

4.92	<H4>	41
4.93	<H5>	42
4.94	<H6>	42
4.95	HOTSPOT.ELEMENTGROUP	43
4.96	<HOTSPOTCHOICE>	43
4.97	<HOTSPOTINTERACTION>	43
4.98	<HOTTEXT>	44
4.99	<HOTTEXTINTERACTION>	44
4.100	<HR>	45
4.101	<HYPERTEXTTELEMENT>	45
4.102	<I>	45
4.103	IDENTIFIER.TYPE	46
4.104	<IMAGEELEMENT>	46
4.105	<IMAGETYPE>	46
4.106		46
4.107	<IMSMD>	46
4.108	<IMSQTIMD>	47
4.109	<INDEX>	47
4.110	INLINE.ELEMENTGROUP	47
4.111	<INLINECHOICE>	47
4.112	<INLINECHOICEINTERACTION>	48
4.113	INLINEINTERACTION.ELEMENTGROUP	48
4.114	INLINESTATIC.ELEMENTGROUP	48
4.115	<INSIDE>	49
4.116	INTEGER.TYPE	49
4.117	<INTEGERDIVIDE>	49
4.118	<INTEGERMODULUS>	49
4.119	<INTEGERTOFloat>	49
4.120	INTERACTION.ELEMENTGROUP	50
4.121	<INTERACTIONTYPE>	50
4.122	INTERACTIONTYPE.TYPE	50
4.123	<ISNULL>	51
4.124	<ITEMBODY>	51
4.125	ITEMSTATISTIC.ELEMENTGROUP	51
4.126	<ITEMTEMPLATE>	51
4.127	<KBD>	51
4.128	LANGUAGE.TYPE	52
4.129	LENGTH.TYPE	52
4.130		52
4.131	<LISTELEMENTS>	52
4.132	<LOMMETADATA>	53
4.133	<LT>	53
4.134	<LTE>	53
4.135	<MAPENTRY>	53
4.136	<MAPRESPONSE>	53
4.137	<MAPRESPONSEPOINT>	54
4.138	<MAPPING>	54
4.139	<MATCH>	54
4.140	M:MATH>	55

4.141	<MATHELEMENT>.....	55
4.142	<MATHVARIABLE>	55
4.143	<MEMBER>	55
4.144	<METADATAPROFILE>.....	55
4.145	MIMETYPE.TYPE	56
4.146	<MODALFEEDBACK>.....	56
4.147	<MULTIPLE>.....	56
4.148	<NOT>	56
4.149	<NULL>.....	57
4.150	<OBJECT>.....	57
4.151	<OBJECTELEMENTS>.....	57
4.152	OBJECTFLOW.ELEMENTGROUP.....	58
4.153	<OBJECTTYPE>.....	58
4.154		58
4.155	<OR>	59
4.156	<ORDERINTERACTION>.....	59
4.157	<ORDERED>	59
4.158	<ORDINARYSTATISTIC>	59
4.159	ORIENTATION.TYPE.....	60
4.160	<OUTCOMEDeCLARATION>	60
4.161	<P>	60
4.162	<PARAM>	61
4.163	PARAMTYPE.TYPE.....	61
4.164	<PATTERNMATCH>	61
4.165	<POSITIONOBJECTINTERACTION>.....	62
4.166	<POSITIONOBJECTSTAGE>.....	62
4.167	<POWER>	62
4.168	<PRE>	62
4.169	<PRESENTATIONELEMENTS>.....	63
4.170	<PRINTEDVARIABLE>	63
4.171	<PRINTEDVARIABLES>	63
4.172	<PRODUCT>.....	64
4.173	<PROMPT>	64
4.174	<Q>	64
4.175	<QTIMETADATA>	65
4.176	<RANDOM>.....	65
4.177	<RANDOMFLOAT>.....	65
4.178	<RANDOMINTEGER>	65
4.179	<REGEXP>.....	66
4.180	<RESPONSECONDITION>	66
4.181	<RESPONSEDECLARATION>	66
4.182	<RESPONSEELSE>.....	67
4.183	<RESPONSEELSEIF>	67
4.184	<RESPONSEIF>.....	67
4.185	<RESPONSEPROCESSING>.....	67
4.186	RESPONSERULE.ELEMENTGROUP	68
4.187	<RESPONSERULES>.....	68
4.188	<ROUND>	68

4.189	<ROUNDING>	68
4.190	ROUNDINGMODE.TYPE	68
4.191	<RPTEMPLATE>	68
4.192	<RUBRIC>	69
4.193	<RUBRICBLOCK>	69
4.194	<SAMP>	69
4.195	<SELECTPOINTINTERACTION>	70
4.196	<SETCORRECTRESPONSE>	70
4.197	<SETDEFAULTVALUE>	70
4.198	<SETOUTCOMEVALUE>	71
4.199	<SETTEMPLATEVALUE>	71
4.200	SHAPE.TYPE	71
4.201	SHOWHIDE.TYPE	71
4.202	SIGN.TYPE	72
4.203	<SIMPLEASSOCIABLECHOICE>	72
4.204	SIMPLEBLOCK.ELEMENTGROUP	72
4.205	<SIMPLECHOICE>	72
4.206	SIMPLEINLINE.ELEMENTGROUP	73
4.207	<SIMPLEMATCHSET>	73
4.208	<SLIDERINTERACTION>	73
4.209	<SMALL>	74
4.210	<SOLUTIONAVAILABLE>	74
4.211		74
4.212	STRING.TYPE	75
4.213	STRING256.TYPE	75
4.214	STRINGINTERACTION.ELEMENTGROUP	75
4.215	<STRINGMATCH>	75
4.216		76
4.217	STYLECLASS.TYPE	76
4.218	<STYLESHEET>	76
4.219	<SUB>	76
4.220	<SUBSTRING>	77
4.221	<SUBTRACT>	77
4.222	<SUM>	77
4.223	<SUP>	78
4.224	<TABLE>	78
4.225	TABLECELL.ELEMENTGROUP	79
4.226	TABLECELLSCOPE.TYPE	79
4.227	<TABLEELEMENTS>	79
4.228	<TARGETOBJECT>	79
4.229	<TBODY>	79
4.230	<TD>	80
4.231	<TEMPLATEBLOCK>	80
4.232	<TEMPLATECONDITION>	81
4.233	<TEMPLATEDECLARATION>	81
4.234	TEMPLATEELEMENT.ELEMENTGROUP	81
4.235	<TEMPLATEELSE>	81
4.236	<TEMPLATEELSEIF>	82
4.237	<TEMPLATEIF>	82

4.238	<TEMPLATEINLINE>	82
4.239	<TEMPLATEPROCESSING>	83
4.240	TEMPLATERULE.ELEMENTGROUP	83
4.241	<TEMPLATES>	83
4.242	<TEXTELEMENTS>	83
4.243	<TEXTENTRYINTERACTION>	83
4.244	<TFOOT>	84
4.245	<TH>	84
4.246	<THEAD>	85
4.247	<TIMEDEPENDENT>	85
4.248	TOLERANCEMODE.TYPE	85
4.249	<TOOLNAME>	85
4.250	<TOOLVENDOR>	85
4.251	<TOOLVERSION>	85
4.252	<TR>	86
4.253	<TRUNCATE>	86
4.254	<TT>	86
4.255		87
4.256	<UPLOADINTERACTION>	87
4.257	URI.TYPE	87
4.258	<USAGEDATA>	88
4.259	<USAGEDATAVOCABULARY>	88
4.260	<VALUE>	88
4.261	<VAR>	88
4.262	<VARIABLE>	89
4.263	VARIABLEDECLARATION.ELEMENTGROUP	89
4.264	VIEW.TYPE	89
ABOUT THIS DOCUMENT		90
LIST OF CONTRIBUTORS		90
REVISION HISTORY		91
INDEX.....		92

1. Introduction

The information model defines a set of classes and data types in an abstract way. When faced with the real task of communicating data between systems these abstract concepts need to be bound to some *physical* representation, such as a stream of bytes in a computer file.

The document describes the required method of binding the information model when the *physical* representation is an XML Document. The binding rules are given primarily in the form of an XML Schema with the following target namespace: http://www.imsglobal.org/xsd/imsqti_v2p0. To assist developers who wish to check the validity of QTI XML documents using tools that support document type definitions (DTDs) the binding rules are also represented as a DTD, however, the DTD is not able to express all the constraints contained in the schema and document instances should validate against the schema. QTI document instances *must* validate against one of the schema or DTD.

1.1 References

- | | |
|--------|---|
| MathML | Mathematical Markup Language (MathML), Version 2.0 (Second Edition)
http://www.w3.org/TR/2003/REC-MathML2-20031021/
Published: 2003-10-21 |
| XHTML | XHTML 1.1: The Extensible HyperText Markup Language |

2. Binding of Complex Types

Complex types, those that contain other objects through composition and/or have attributes, are represented in the schema as elements with complex content in a straightforward way. Classes that are used as base classes (typically labeled *abstract* in the model) are used to define an element group consisting of a single choice listing all the non-abstract classes derived from them. Classes with attributes are used to define attribute groups and those that contain other objects (including through inheritance) are used to define element groups describing them.

Elements defined by [XHTML] are *not* imported directly from an external schema but are instead re-declared as part of the QTI schema. At the time of writing the use of schema for XHTML is at an experimental stage. However, the math element defined by [MathML] *is* imported from the MathML schema. Note that the use of the MathML schema excludes the use of the entity declarations for mathematical symbols defined in the original MathML DTD and therefore these should not be used for referring to characters within QTI document instances.

3. Binding of Simple Types

Simple datatypes are bound directly to the closest equivalent type in XML Schema, for example, boolean is bound directly to `xsd:boolean`. Enumerations are bound as enumerated restrictions of `xsd:NMTOKEN`.

The information model says nothing about how simple types are to be represented in text. For example, the boolean type is an abstract boolean which can be either logically true or logically false. By binding these simple types using XML Schema they automatically inherit the lexical bindings described there. A lexical binding is just a set of rules for representing the abstract type as a run of text characters. For example, XML Schema allows the following strings to represent the values of `xsd:boolean`: "true", "false", "1" and "0".

XML DTDs have a smaller vocabulary for defining simple types and is therefore not able to impose the same lexical constraints as the schema. Applications that generate QTI document instances that validate against the DTD must still use the same lexical bindings defined by schema even though these will not be checked automatically by the XML parser. For example, in the DTD the boolean type is bound only to NMTOKEN and therefore the XML parser will permit many more strings than the four listed above. However, strings such as "yes" and "no" are still forbidden.

4. XML Binding Reference

4.1 <a>

Description: Defined by XHTML

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **href (required).** Data type = uri.Type
- **type (optional).** Data type = mimeType.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.2 <abbr>

Description: Defined by XHTML

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.3 <acronym>

Description: Defined by XHTML

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.4 <adaptive>

Description: Profile flag for the adaptive items feature.

Context:

- Occurs [1] within contentProfile

4.5 <address>

Description: Defined by XHTML

Context:

See:

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inline.ElementGroup

- PCDATA

4.6 <and>

Description: An expression that performs a boolean and.

Context:

See:

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.7 <anyN>

Description: An expression for testing groups of boolean sub-expressions.

Context:

See:

- expression.ElementGroup

Attributes:

- **min (required).** Data type = integer.Type
- **max (required).** Data type = integer.Type

Elements:

- Members of expression.ElementGroup

4.8 <areaMapEntry>

Description: Defines an area for mapping a set of points onto a single real number.

Context:

- Occurs [1..*] within areaMapping

Attributes:

- **shape (required).** Data type = shape.Type
- **coords (required).** Data type = coords.Type
- **mappedValue (required).** Data type = float.Type

4.9 <areaMapping>

Description: Defines a mapping from the set of points to real numbers using areas.

Context:

- Occurs [0..1] within responseDeclaration

Attributes:

- **lowerBound (optional).** Data type = float.Type

- **upperBound (optional)**. Data type = float.Type
- **defaultValue (required)**. Data type = float.Type

Elements:

- <areaMapEntry>

4.10 <assessmentItem>

Description: The root element for QTI items

Context:

Can be the root element of an XML document.

Attributes:

- **identifier (required)**. Data type = string.Type
- **title (required)**. Data type = string.Type
- **label (optional)**. Data type = string256.Type
- **xml:lang (optional)**.
- **adaptive (required)**. Data type = boolean.Type
- **timeDependent (required)**. Data type = boolean.Type
- **toolName (optional)**. Data type = string256.Type
- **toolVersion (optional)**. Data type = string256.Type

Elements:

- <responseDeclaration>
- <outcomeDeclaration>
- <templateDeclaration>
- <templateProcessing>
- <stylesheet>
- <itemBody>
- <responseProcessing>
- <modalFeedback>

4.11 associableChoice.ElementGroup

Description: The group of elements that are used in association-type interactions.

Group members: <associableHotspot>, <gap>, <gapImg>, <gapText>, <simpleAssociableChoice>

Context:

Not applicable.

4.12 <associableHotspot>

Description: An element that defines a hot area of a graphic for association tasks.

Context:

- Occurs [1..*] within graphicAssociateInteraction
- Occurs [1..*] within graphicGapMatchInteraction

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type
- **identifier (required)**. Data type = identifier.Type
- **fixed (optional)**. Data type = boolean.Type
- **matchGroup (optional)**. Data type = list of identifier.Type
- **shape (required)**. Data type = shape.Type
- **coords (required)**. Data type = coords.Type
- **hotspotLabel (optional)**. Data type = string256.Type
- **matchMax (required)**. Data type = integer.Type

4.13 <associateInteraction>

Description: Interaction in which the candidate must identify pairs of choices from a single set.

Context:**See:**

- block.ElementGroup
- flow.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type
- **responseIdentifier (required)**. Data type = identifier.Type
- **shuffle (required)**. Data type = boolean.Type
- **maxAssociations (required)**. Data type = integer.Type

Elements:

- <prompt>
- <simpleAssociableChoice>

4.14 atomicBlock.ElementGroup

Description: A group of elements that provide structure but that can only contain elements behaving like spans of text.

Group members: <address>, <h1>, <h2>, <h3>, <h4>, <h5>, <h6>, <p>, <pre>

Context:**See:**

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup

- objectFlow.ElementGroup

4.15 atomicInline.ElementGroup

Description: A group of empty elements that behave like spans of text

Group members:
,

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

4.16

Description: Defined by XHTML

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.17 <bankProfile>

Description: An element for describing the capabilities or requirements of an item-bank system.

Context:

Can be the root element of an XML document.

Elements:

- <usageDataVocabulary>
- <metadataProfile>
- Elements from other namespaces

4.18 baseType.Type

One of the following symbolic values:

- boolean
- directedPair
- duration
- file
- float
- identifier
- integer
- pair
- point
- string
- uri

4.19 <baseValue>

Description: A simple expression returning a constant value of the given base-type.

Context:

See:

- expression.ElementGroup

Attributes:

- **baseType (required).** Data type = baseType.Type

4.20 <big>

Description: Defined by XHTML

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.21 block.ElementGroup

Description: A group of elements that provide structure to the item body.

Group members: <address>, <associateInteraction>, <blockquote>, <choiceInteraction>, <customInteraction>, <div>, <dl>, <drawingInteraction>, <extendedTextInteraction>, <feedbackBlock>, <gapMatchInteraction>, <graphicAssociateInteraction>, <graphicGapMatchInteraction>, <graphicOrderInteraction>, <h1>, <h2>, <h3>, <h4>, <h5>, <h6>, <hotspotInteraction>, <hottextInteraction>, <hr>, <m:math>, <matchInteraction>, , <orderInteraction>, <p>, <positionObjectStage>, <pre>, <rubricBlock>, <selectPointInteraction>, <sliderInteraction>, <table>, <templateBlock>, , <uploadInteraction>

Context:

- Occurs [*] within itemBody
- Occurs [*] within members of simpleBlock.ElementGroup

4.22 blockInteraction.ElementGroup

Description: The group of interactions which have inherent structure of their own.

Group members: <associateInteraction>, <choiceInteraction>, <drawingInteraction>, <extendedTextInteraction>, <gapMatchInteraction>, <graphicAssociateInteraction>, <graphicGapMatchInteraction>, <graphicOrderInteraction>, <hotspotInteraction>, <hottextInteraction>, <matchInteraction>, <orderInteraction>, <selectPointInteraction>, <sliderInteraction>, <uploadInteraction>

Context:

See:

- block.ElementGroup
- flow.ElementGroup
- objectFlow.ElementGroup

4.23 blockStatic.ElementGroup

Description: A group of elements that provide structure excluding interactions.

Group members: <address>, <blockquote>, <div>, <dl>, <feedbackBlock>, <h1>, <h2>, <h3>, <h4>, <h5>, <h6>, <hr>, <m:math>, , <p>, <pre>, <rubricBlock>, <table>, <templateBlock>,

Context:

- Occurs [1..*] within gapMatchInteraction
- Occurs [1..*] within hottextInteraction
- Occurs [*] within templateBlock

See:

- block.ElementGroup

4.24 <blockquote>

Description: Defined by XHTML

Context:

See:

- block.ElementGroup

- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **cite (optional).** Data type = uri.Type

Elements:

- Members of block.ElementGroup

4.25 bodyElement.ElementGroup

Description: The group of elements used to describe the structure, material and interactions within the item body.

Group members: <a>, <abbr>, <acronym>, <address>, <associableHotspot>, <associateInteraction>, , <big>, <blockquote>,
, <caption>, <choiceInteraction>, <cite>, <code>, <col>, <colgroup>, <customInteraction>, <dd>, <dfn>, <div>, <dl>, <drawingInteraction>, <dt>, , <endAttemptInteraction>, <extendedTextInteraction>, <feedbackBlock>, <feedbackInline>, <gap>, <gapImg>, <gapMatchInteraction>, <gapText>, <graphicAssociateInteraction>, <graphicGapMatchInteraction>, <graphicOrderInteraction>, <h1>, <h2>, <h3>, <h4>, <h5>, <h6>, <hotspotChoice>, <hotspotInteraction>, <hottext>, <hottextInteraction>, <hr>, <i>, , <inlineChoice>, <inlineChoiceInteraction>, <itemBody>, <kbd>, , <matchInteraction>, <object>, , <orderInteraction>, <p>, <positionObjectInteraction>, <pre>, <printedVariable>, <prompt>, <q>, <rubricBlock>, <samp>, <selectPointInteraction>, <simpleAssociableChoice>, <simpleChoice>, <sliderInteraction>, <small>, , , <sub>, <sup>, <table>, <tbody>, <td>, <templateBlock>, <templateInline>, <textEntryInteraction>, <tfoot>, <th>, <thead>, <tr>, <tt>, , <uploadInteraction>, <var>

Context:

Not applicable.

4.26 boolean.Type

A trivial restriction of xsd:boolean.

4.27

Description: Defined by XHTML

Context:**See:**

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

4.28 <caption>

Description: Defined by XHTML

Context:

- Occurs [0..1] within table

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.29 cardinality.Type

One of the following symbolic values:

- multiple
- ordered
- record
- single

4.30 <categorizedStatistic>

Description: A categorized statistic, such as a score-conversion table, expressed as a mapping.

Context:

See:

- itemStatistic.ElementGroup

Attributes:

- **name (required)**. Data type = identifier.Type
- **glossary (optional)**. Data type = uri.Type
- **context (required)**. Data type = uri.Type
- **caseCount (optional)**. Data type = integer.Type
- **stdError (optional)**. Data type = float.Type
- **stdDeviation (optional)**. Data type = float.Type
- **lastUpdated (optional)**. Data type = date.Type

Elements:

- <targetObject>
- <mapping>

4.31 choice.ElementGroup

Description: The group of elements that provide choices from which the candidate may select a response.

Group members: <associableHotspot>, <gap>, <gapImg>, <gapText>, <hotspotChoice>, <hottext>, <inlineChoice>, <simpleAssociableChoice>, <simpleChoice>

Context:

Not applicable.

4.32 <choiceInteraction>

Description: The element that represents simple multiple choice and multiple-response interactions.

Context:

See:

- block.ElementGroup
- flow.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **responseIdentifier (required).** Data type = identifier.Type
- **shuffle (required).** Data type = boolean.Type
- **maxChoices (required).** Data type = integer.Type

Elements:

- <prompt>
- <simpleChoice>

4.33 <cite>

Description: Defined by XHTML

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.34 <code>

Description: Defined by XHTML

Context:**See:**

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.35 <col>

Description: Defined by XHTML

Context:

- Occurs [*] within colgroup
- Occurs [*] within table

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

4.36 <colgroup>

Description: Defined by XHTML

Context:

- Occurs [*] within table

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- <col>

4.37 <composite>

Description: Profile flag for the composite items feature.

Context:

- Occurs [1] within contentProfile
- Occurs [0..1] within qtiMetadata

4.38 <contains>

Description: An expression that tests a container to determine if it contains another.

Context:**See:**

- expression.ElementGroup

Elements:

- Members of [expression.ElementGroup](#)

4.39 <contentProfile>

Description: An element for describing the capabilities or requirements of a system that handles QTI content.

Context:

Can be the root element of an XML document.

Elements:

- <composite>
- <adaptive>
- <timeDependent>
- <templates>
- <textElements>
- <listElements>
- <objectElements>
- <objectType>
- <presentationElements>
- <tableElements>

- <imageElement>
- <imageType>
- <hypertextElement>
- <mathElement>
- <mathVariable>
- <feedbackIntegrated>
- <feedbackModal>
- <rubric>
- <printedVariables>
- <interactionType>
- <responseRules>
- <rpTemplate>
- <rounding>
- <regexp>
- <metadataProfile>
- Elements from other namespaces

4.40 coords.Type

A trivial restriction of xsd:string.

4.41 <correct>

Description: A simple expression returning the correct value associated with a response variable.

Context:

See:

- expression.ElementGroup

Attributes:

- **identifier (required).** Data type = identifier.Type

4.42 <correctResponse>

Description: Declares the (or a) correct response for a response variable.

Context:

- Occurs [0..1] within responseDeclaration

Attributes:

- **interpretation (optional).** Data type = string.Type

Elements:

- <value>

4.43 <customInteraction>

Description: An element that allows extensions to QTI to be developed for interaction types not covered by the information model.

Context:**See:**

- block.ElementGroup
- flow.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type
- **responseIdentifier (required)**. Data type = identifier.Type
- Attributes from other namespaces

Elements:

- Elements from any namespace

4.44 <customOperator>

Description: An element allowing externally defined expressions to be used.

Context:**See:**

- expression.ElementGroup

Attributes:

- **class (optional)**. Data type = identifier.Type
- **definition (optional)**. Data type = uri.Type
- Attributes from other namespaces

Elements:

- Members of expression.ElementGroup

4.45 date.Type

A trivial restriction of xsd:date.

4.46 <dd>

Description: Defined by XHTML

Context:**See:**

- dlElement.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type

- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of flow.ElementGroup
- PCDATA

4.47 <default>

Description: A simple expression returning the default value of an item variable.

Context:**See:**

- expression.ElementGroup

Attributes:

- **identifier (required).** Data type = identifier.Type

4.48 <defaultValue>

Description: Defines the default value for an item variable.

Context:

- Occurs [0..1] within members of variableDeclaration.ElementGroup

Attributes:

- **interpretation (optional).** Data type = string.Type

Elements:

- <value>

4.49 <delete>

Description: An expression that derives a new container by removing a given value from an existing one.

Context:**See:**

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.50 <dfn>

Description: Defined by XHTML

Context:**See:**

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.51 <div>

Description: Defined by XHTML

Context:**See:**

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- Members of flow.ElementGroup
- PCDATA

4.52 <divide>

Description: An expression for dividing one number by another.

Context:**See:**

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.53 <dl>

Description: Defined by XHTML

Context:

See:

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of dlElement.ElementGroup

4.54 dlElement.ElementGroup

Description: Elements that can appear within <dl>.

Group members: <dd>, <dt>

Context:

- Occurs [*] within dl

4.55 <drawingInteraction>

Description: Interaction in which the candidate draws freely on a given backdrop image.

Context:

See:

- block.ElementGroup
- flow.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **responseIdentifier (required).** Data type = identifier.Type

Elements:

- <prompt>

- <object>

4.56 <dt>

Description: Defined by XHTML

Context:

See:

- dlElement.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.57 <durationGTE>

Description: An expression for testing the greater-than-or-equal relation between two durations.

Context:

See:

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.58 <durationLT>

Description: An expression for testing the less-than relation between two durations.

Context:

See:

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.59

Description: Defined by XHTML

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.60 <endAttemptInteraction>

Description: A special interaction for providing alternative ways to end an attempt.

Context:**See:**

- flow.ElementGroup
- inline.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type
- **responseIdentifier (required)**. Data type = identifier.Type
- **title (required)**. Data type = string.Type

4.61 <equal>

Description: An expression for testing two numeric values for equality.

Context:**See:**

- expression.ElementGroup

Attributes:

- **toleranceMode (required)**. Data type = toleranceMode.Type
- **tolerance (optional)**. Data type = list of float.Type

Elements:

- Members of expression.ElementGroup

4.62 <equalRounded>

Description: An expression for testing two numeric values for equality after rounding.

Context:

See:

- expression.ElementGroup

Attributes:

- **roundingMode (required).** Data type = roundingMode.Type
- **figures (required).** Data type = integer.Type

Elements:

- Members of expression.ElementGroup

4.63 <exitResponse>

Description: A response rule that terminates response processing immediately.

Context:

See:

- responseRule.ElementGroup

4.64 <exitTemplate>

Description: A template rule that terminates template processing immediately.

Context:

See:

- templateRule.ElementGroup

4.65 expression.ElementGroup

Description: The group of elements that are used to create expressions for setting variable values and controlling conditional groups of rules.

Group members: <and>, <anyN>, <baseValue>, <contains>, <correct>, <customOperator>, <default>, <delete>, <divide>, <durationGTE>, <durationLT>, <equal>, <equalRounded>, <fieldValue>, <gt>, <gte>, <index>, <inside>, <integerDivide>, <integerModulus>, <integerToFloat>, <isNull>, <lt>, <lte>, <mapResponse>, <mapResponsePoint>, <match>, <member>, <multiple>, <not>, <null>, <or>, <ordered>, <patternMatch>, <power>, <product>, <random>, <randomFloat>, <randomInteger>, <round>, <stringMatch>, <substring>, <subtract>, <sum>, <truncate>, <variable>

Context:

- Occurs [1..*] within and
- Occurs [1..*] within anyN
- Occurs [2] within contains
- Occurs [*] within customOperator
- Occurs [2] within delete
- Occurs [2] within divide

- Occurs [2] within durationGTE
- Occurs [2] within durationLT
- Occurs [2] within equal
- Occurs [2] within equalRounded
- Occurs [1] within fieldValue
- Occurs [2] within gt
- Occurs [2] within gte
- Occurs [1] within index
- Occurs [1] within inside
- Occurs [2] within integerDivide
- Occurs [2] within integerModulus
- Occurs [1] within integerToFloat
- Occurs [1] within isNull
- Occurs [2] within lt
- Occurs [2] within lte
- Occurs [2] within match
- Occurs [2] within member
- Occurs [*] within multiple
- Occurs [1] within not
- Occurs [1..*] within or
- Occurs [*] within ordered
- Occurs [1] within patternMatch
- Occurs [2] within power
- Occurs [1..*] within product
- Occurs [1] within random
- Occurs [1] within responseElseIf
- Occurs [1] within responseIf
- Occurs [1] within round
- Occurs [1] within setCorrectResponse
- Occurs [1] within setDefaultValue
- Occurs [1] within setOutcomeValue
- Occurs [1] within setTemplateValue
- Occurs [2] within stringMatch
- Occurs [2] within substring
- Occurs [2] within subtract
- Occurs [1..*] within sum
- Occurs [1] within templateElseIf
- Occurs [1] within templateIf
- Occurs [1] within truncate

4.66 <extendedTextInteraction>

Description: Interaction that allows the candidate to supply an extended free-text response.

Context:

See:

- block.ElementGroup
- flow.ElementGroup

- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type
- **responseIdentifier (required)**. Data type = identifier.Type
- **base (optional)**. Data type = integer.Type
- **stringIdentifier (optional)**. Data type = identifier.Type
- **expectedLength (optional)**. Data type = integer.Type
- **patternMask (optional)**. Data type = string.Type
- **placeholderText (optional)**. Data type = string.Type
- **maxStrings (optional)**. Data type = integer.Type
- **expectedLines (optional)**. Data type = integer.Type

Elements:

- <prompt>

4.67 <feedbackBlock>

Description: A structural part of the item body whose visibility can be conditionally controlled by the current outcomes.

Context:

See:

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **outcomeIdentifier (required)**. Data type = identifier.Type
- **showHide (required)**. Data type = showHide.Type
- **identifier (required)**. Data type = identifier.Type
- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- Members of block.ElementGroup

4.68 feedbackElement.ElementGroup

Description: Elements whose visibility can be conditionally controlled depending on the current outcomes.

Group members: <feedbackBlock>, <feedbackInline>

Context:

Not applicable.

4.69 <feedbackInline>

Description: A span of text (or equivalent) whose visibility can be conditionally controlled by the current outcomes.

Context:**See:**

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **outcomeIdentifier (required).** Data type = identifier.Type
- **showHide (required).** Data type = showHide.Type
- **identifier (required).** Data type = identifier.Type
- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.70 <feedbackIntegrated>

Description: Profile flag for the integrated feedback feature.

Context:

- Occurs [1] within contentProfile

4.71 <feedbackModal>

Description: Profile flag for the modal feedback feature.

Context:

- Occurs [1] within contentProfile

4.72 <feedbackType>

Context:

- Occurs [0..1] within qtiMetadata

Content: a value of type feedbackType.Type.

4.73 feedbackType.Type

One of the following symbolic values:

- adaptive
- nonadaptive
- none

4.74 <fieldValue>

Description: An expression that extracts a single field value from a record container.

Context:

See:

expression.ElementGroup

Attributes:

- **fieldIdentifier (required).** Data type = identifier.Type

Elements:

- Members of expression.ElementGroup

4.75 float.Type

A trivial restriction of xsd:float.

4.76 flow.ElementGroup

Description: A group of elements that can appear in contexts where either further structure or spans of text are allowed.

Group members: <a>, <abbr>, <acronym>, <address>, <associateInteraction>, , <big>, <blockquote>,
, <choiceInteraction>, <cite>, <code>, <customInteraction>, <dfn>, <div>, <dl>, <drawingInteraction>, , <endAttemptInteraction>, <extendedTextInteraction>, <feedbackBlock>, <feedbackInline>, <gapMatchInteraction>, <graphicAssociateInteraction>, <graphicGapMatchInteraction>, <graphicOrderInteraction>, <h1>, <h2>, <h3>, <h4>, <h5>, <h6>, <hotspotInteraction>, <hottext>, <hottextInteraction>, <hr>, <i>, , <inlineChoiceInteraction>, <kbd>, <m:math>, <matchInteraction>, <object>, , <orderInteraction>, <p>, <pre>, <printedVariable>, <q>, <rubricBlock>, <samp>, <selectPointInteraction>, <sliderInteraction>, <small>, , , <sub>, <sup>, <table>, <templateBlock>, <templateInline>, <textEntryInteraction>, <tt>, , <uploadInteraction>, <var>

Context:

- Occurs [*] within dd
- Occurs [*] within div
- Occurs [*] within li
- Occurs [*] within members of tableCell.ElementGroup

See:

- objectFlow.ElementGroup

4.77 flowStatic.ElementGroup

Description: A group of elements that can appear in contexts where either further structure or spans of text are allowed excluding interactions.

Group members: <a>, <abbr>, <acronym>, <address>, , <big>, <blockquote>,
, <cite>, <code>, <dfn>, <div>, <dl>, , <feedbackBlock>, <feedbackInline>, <h1>, <h2>, <h3>, <h4>, <h5>, <h6>, <hottext>, <hr>, <i>, , <kbd>, <m:math>, <object>, , <p>, <pre>, <printedVariable>, <q>, <rubricBlock>, <samp>, <small>, , , <sub>, <sup>, <table>, <templateBlock>, <templateInline>, <tt>, , <var>

Context:

- Occurs [*] within modalFeedback
- Occurs [*] within simpleAssociableChoice
- Occurs [*] within simpleChoice

See:

- flow.ElementGroup
- objectFlow.ElementGroup

4.78 <gap>

Description: Defines the position of a gap in the text for gap-filling tasks.

Context:

See:

- inline.ElementGroup
- inlineStatic.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **identifier (required).** Data type = identifier.Type
- **fixed (optional).** Data type = boolean.Type
- **matchGroup (optional).** Data type = list of identifier.Type

4.79 gapChoice.ElementGroup

Description: A group of elements that can be used to define choices for gap-filling tasks.

Group members: <gapImg>, <gapText>

Context:

- Occurs [1..*] within gapMatchInteraction

4.80 <gapImg>

Description: An image that can be used to fill a gap.

Context:

- Occurs [1..*] within graphicGapMatchInteraction

See:

- gapChoice.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type
- **identifier (required)**. Data type = identifier.Type
- **fixed (optional)**. Data type = boolean.Type
- **matchGroup (optional)**. Data type = list of identifier.Type
- **matchMax (required)**. Data type = integer.Type
- **objectLabel (optional)**. Data type = string.Type

Elements:

- <object>

4.81 <gapMatchInteraction>

Description: An interaction in which the candidate fills gaps in a passage of text from a set of predefined choices.

Context:

See:

- block.ElementGroup
- flow.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type
- **responseIdentifier (required)**. Data type = identifier.Type
- **shuffle (required)**. Data type = boolean.Type

Elements:

- <prompt>
- Members of gapChoice.ElementGroup
- Members of blockStatic.ElementGroup

4.82 <gapText>

Description: A simple run of text that can be used to fill a gap.

Context:

See:

- gapChoice.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type
- **identifier (required)**. Data type = identifier.Type
- **fixed (optional)**. Data type = boolean.Type
- **matchGroup (optional)**. Data type = list of identifier.Type
- **matchMax (required)**. Data type = integer.Type

4.83 <graphicAssociateInteraction>

Description: Interaction in which the candidate associates pairs of pre-defined hotspots on an image.

Context:**See:**

- block.ElementGroup
- flow.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type
- **responseIdentifier (required)**. Data type = identifier.Type
- **maxAssociations (required)**. Data type = integer.Type

Elements:

- <prompt>
- <object>
- <associableHotspot>

4.84 <graphicGapMatchInteraction>

Description: Interaction in which the candidate fills gaps within a given image, e.g., through drag-and-drop.

Context:**See:**

- block.ElementGroup
- flow.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

- **responseIdentifier (required).** Data type = identifier.Type

Elements:

- <prompt>
- <object>
- <gapImg>
- <associableHotspot>

4.85 graphicInteraction.ElementGroup

Description: A group of elements for describing image-based tasks.

Group members: <graphicAssociateInteraction>, <graphicGapMatchInteraction>, <graphicOrderInteraction>, <hotspotInteraction>, <selectPointInteraction>

Context:**See:**

- block.ElementGroup
- flow.ElementGroup
- objectFlow.ElementGroup

4.86 <graphicOrderInteraction>

Description: Interaction in which the candidate orders a set of predefined hotspots on an image.

Context:**See:**

- block.ElementGroup
- flow.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **responseIdentifier (required).** Data type = identifier.Type

Elements:

- <prompt>
- <object>
- <hotspotChoice>

4.87 <gt>

Description: An expression for testing the greater-than relation between two numbers.

Context:**See:**

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.88 <gte>

- **Description:** An expression for testing the greater-than-or-equal relation between two numbers.

Context:**See:**

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.89 <h1>

Description: Defined by XHTML

Context:**See:**

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.90 <h2>

Description: Defined by XHTML

Context:**See:**

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup

- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.91 <h3>

Description: Defined by XHTML

Context:**See:**

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.92 <h4>

Description: Defined by XHTML

Context:**See:**

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type

- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.93 <h5>

Description: Defined by XHTML

Context:**See:**

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.94 <h6>

Description: Defined by XHTML

Context:**See:**

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inline.ElementGroup

- PCDATA

4.95 hotspot.ElementGroup

Description: A group of elements that define hot areas of a graphic.

Group members: <associableHotspot>, <hotspotChoice>

Context:

Not applicable.

4.96 <hotspotChoice>

Description: An element that defines a hot area of a graphic for simple area selection tasks.

Context:

- Occurs [1..*] within graphicOrderInteraction
- Occurs [1..*] within hotspotInteraction

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **identifier (required).** Data type = identifier.Type
- **fixed (optional).** Data type = boolean.Type
- **shape (required).** Data type = shape.Type
- **coords (required).** Data type = coords.Type
- **hotspotLabel (optional).** Data type = string256.Type

4.97 <hotspotInteraction>

Description: Interaction in which the candidate selects pre-defined hotspots on an image.

Context:

See:

- block.ElementGroup
- flow.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **responseIdentifier (required).** Data type = identifier.Type
- **maxChoices (required).** Data type = integer.Type

Elements:

- <prompt>
- <object>
- <hotspotChoice>

4.98 <hottext>

Description: Defines an area of hottext for hottext selection tasks.

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **identifier (required).** Data type = identifier.Type
- **fixed (optional).** Data type = boolean.Type

Elements:

- Members of inlineStatic.ElementGroup
- PCDATA

4.99 <hottextInteraction>

Description: Interaction in which the candidate selects pre-defined hot areas within the text.

Context:

See:

- block.ElementGroup
- flow.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **responseIdentifier (required).** Data type = identifier.Type
- **maxChoices (required).** Data type = integer.Type

Elements:

- <prompt>
- Members of blockStatic.ElementGroup

4.100 <hr>

Description: Defined by XHTML

Context:

See:

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

4.101 <hypertextElement>

Description: Profile flag for the XHTML hypertext element.

Context:

- Occurs [1] within contentProfile

4.102 <i>

Description: Defined by XHTML

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.103 identifier.Type

A trivial restriction of xsd:NMTOKEN.

4.104 <imageElement>

Description: Profile flag for the XHTML image element.

Context:

- Occurs [1] within contentProfile

4.105 <imageType>

Description: Profile element for identifying a specific image mime-type.

Context:

- Occurs [*] within contentProfile

4.106

Description: Defined by XHTML

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **src (required).** Data type = uri.Type
- **alt (required).** Data type = string256.Type
- **longdesc (optional).** Data type = uri.Type
- **height (optional).** Data type = length.Type
- **width (optional).** Data type = length.Type

4.107 <imsmd>

Description: Profile flag for IMS meta-data.

Context:

- Occurs [1] within metadataProfile

4.108 <imsqtimd>

Description: Profile flag for IMS QTI meta-data.

Context:

- Occurs [1] within metadataProfile

4.109 <index>

Description: An expression that extracts a single value from an ordered container.

Context:

See:

- expression.ElementGroup

Attributes:

n (required). Data type = integer.Type

Elements:

Members of expression.ElementGroup

4.110 inline.ElementGroup

Description: The group of elements that behave like spans of text.

Group members: <a>, <abbr>, <acronym>, , <big>,
, <cite>, <code>, <dfn>, , <endAttemptInteraction>, <feedbackInline>, <gap>, <hottext>, <i>, , <inlineChoiceInteraction>, <kbd>, <m:math>, <object>, <printedVariable>, <q>, <samp>, <small>, , , <sub>, <sup>, <templateInline>, <textEntryInteraction>, <tt>, <var>

Context:

- Occurs [*] within members of atomicBlock.ElementGroup
- Occurs [*] within caption
- Occurs [*] within dt
- Occurs [*] within members of simpleInline.ElementGroup

4.111 <inlineChoice>

Description: A string of text that can be used to fill a gap.

Context:

- Occurs [1..*] within inlineChoiceInteraction

Attributes:

- id (optional).** Data type = identifier.Type
- class (optional).** Data type = list of styleclass.Type
- xml:lang (optional).**
- label (optional).** Data type = string256.Type
- identifier (required).** Data type = identifier.Type
- fixed (optional).** Data type = boolean.Type

4.112 <inlineChoiceInteraction>

Description: An interaction that allows a single gap in the text to be filled from a set of predefined strings.

Context:

See:

- flow.ElementGroup
- inline.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **responseIdentifier (required).** Data type = identifier.Type
- **shuffle (required).** Data type = boolean.Type

Elements:

- <inlineChoice>

4.113 inlineInteraction.ElementGroup

Description: The group of interactions that behave like spans of text.

Group members: <endAttemptInteraction>, <inlineChoiceInteraction>, <textEntryInteraction>

Context:

See:

- flow.ElementGroup
- inline.ElementGroup
- objectFlow.ElementGroup

4.114 inlineStatic.ElementGroup

Description: A group of elements that behave like spans of text excluding interactions.

Group members: <a>, <abbr>, <acronym>, , <big>,
, <cite>, <code>, <dfn>, , <feedbackInline>, <gap>, <hottext>, <i>, , <kbd>, <m:math>, <object>, <printedVariable>, <q>, <samp>, <small>, , , <sub>, <sup>, <templateInline>, <tt>, <var>

Context:

- Occurs [*] within hottext
- Occurs [*] within prompt
- Occurs [*] within templateInline

See:

- inline.ElementGroup

4.115 <inside>

Description: An expression for testing if a point is inside a given area.

Context:

See:

- expression.ElementGroup

Attributes:

- **shape (required).** Data type = shape.Type
- **coords (required).** Data type = coords.Type

Elements:

- Members of expression.ElementGroup

4.116 integer.Type

A trivial restriction of xsd:integer.

4.117 <integerDivide>

Description: An expression for performing integer-division.

Context:

See:

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.118 <integerModulus>

Description: An expression for calculating the remainder following integer-division.

Context:

See:

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.119 <integerToFloat>

Description: An expression for converting an integer to the corresponding value of float base-type.

Context:

See:

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.120 interaction.ElementGroup

Description: The group of elements that allow the candidate to interact with the item, setting or updating the values of the response variables.

Group members: <associateInteraction>, <choiceInteraction>, <customInteraction>, <drawingInteraction>, <endAttemptInteraction>, <extendedTextInteraction>, <gapMatchInteraction>, <graphicAssociateInteraction>, <graphicGapMatchInteraction>, <graphicOrderInteraction>, <hotspotInteraction>, <hottextInteraction>, <inlineChoiceInteraction>, <matchInteraction>, <orderInteraction>, <positionObjectInteraction>, <selectPointInteraction>, <sliderInteraction>, <textEntryInteraction>, <uploadInteraction>

Context:

Not applicable.

4.121 <interactionType>

Context:

- Occurs [*] within contentProfile
- Occurs [*] within qtiMetadata

Content: a value of type interactionType.Type.

4.122 interactionType.Type

One of the following symbolic values:

- associateInteraction
- choiceInteraction
- customInteraction
- drawingInteraction
- endAttemptInteraction
- extendedTextInteraction
- gapMatchInteraction
- graphicAssociateInteraction
- graphicGapMatchInteraction
- graphicOrderInteraction
- hotspotInteraction
- hottextInteraction
- inlineChoiceInteraction
- matchInteraction
- orderInteraction
- positionObjectInteraction
- selectPointInteraction
- sliderInteraction
- textEntryInteraction
- uploadInteraction

4.123 <isNull>

Description: An expression that tests for the NULL value.

Context:

See:

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.124 <itemBody>

Description: Describes the body of an item, the text, graphics and interactions that are presented to the candidate.

Context:

- Occurs [0..1] within assessmentItem

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of block.ElementGroup

4.125 itemStatistic.ElementGroup

Description: A group of elements used to define item statistics.

Group members: <categorizedStatistic>, <ordinaryStatistic>

Context:

- Occurs [*] within usageData

4.126 <itemTemplate>

Description: A meta-data flag indicating that the item is a template.

Context:

- Occurs [0..1] within qtiMetadata

4.127 <kbd>

Description: Defined by XHTML

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.128 language.Type

A trivial restriction of xsd:string.

4.129 length.Type

A trivial restriction of xsd:string.

4.130

Description: Defined by XHTML

Context:

- Occurs [*] within ol
- Occurs [*] within ul

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- Members of flow.ElementGroup
- PCDATA

4.131 <listElements>

Description: Profile flag for the XHTML list elements.

Context:

- Occurs [1] within contentProfile

4.132 <lomMetadata>

Description: Profile flag for LOM meta-data.

Context:

- Occurs [1] within metadataProfile

4.133 <lt>

Description: An expression for testing the less-than relation between two numbers.

Context:

See:

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.134 <lte>

Description: An expression for testing the less-than-or-equal relation between two numbers.

Context:

See:

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.135 <mapEntry>

Description: Defines a mapping from a single value, the key, onto a real number.

Context:

- Occurs [1..*] within mapping

Attributes:

- **mapKey (required).** Data type = xsd:string
- **mappedValue (required).** Data type = float.Type

4.136 <mapResponse>

Description: An expression for mapping the value(s) of a response variable onto a real number using the declared mapping.

Context:

See:

- expression.ElementGroup

Attributes:

- **identifier (required)**. Data type = identifier.Type

4.137 <mapResponsePoint>

Description: An expression for mapping the value(s) of a point-type response variable onto a real number using the declared area-mapping.

Context:**See:**

- expression.ElementGroup

Attributes:

- **identifier (required)**. Data type = identifier.Type

4.138 <mapping>

Description: Defines a mapping from a source set of values onto real numbers.

Context:

- Occurs [1] within categorizedStatistic
- Occurs [0..1] within responseDeclaration

Attributes:

- **lowerBound (optional)**. Data type = float.Type
- **upperBound (optional)**. Data type = float.Type
- **defaultValue (required)**. Data type = float.Type

Elements:

- <mapEntry>

4.139 <match>

Description: An expression for testing if two values are identical.

Context:**See:**

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

<matchInteraction>

Description: Interaction in which the candidate must identify pairs of choices between two distinct sets.

Context:**See:**

- block.ElementGroup

- flow.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type
- **responseIdentifier (required)**. Data type = identifier.Type
- **shuffle (required)**. Data type = boolean.Type
- **maxAssociations (required)**. Data type = integer.Type

Elements:

- <prompt>
- <simpleMatchSet>

4.140 m:math>

Externally defined.

4.141 <mathElement>

Description: Profile flag for the MathML math element.

Context:

- Occurs [1] within contentProfile

4.142 <mathVariable>

Description: Profile flag for the mathVariable feature.

Context:

- Occurs [1] within contentProfile

4.143 <member>

Description: An expression that tests a container to determine if it contains a given value.

Context:**See:**

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.144 <metadataProfile>

Description: An element for describing the capabilities or requirements of a system with respect to meta-data.

Context:

- Occurs [1] within bankProfile
- Occurs [1] within contentProfile

Elements:

- <imsmd>
- <lomMetadata>
- <imsqtimd>

4.145 mimeType.Type

A trivial restriction of xsd:string.

4.146 <modalFeedback>

Description: Feedback conditionally shown to the candidate directly following response processing depending on the value of the given outcome variable.

Context:

- Occurs [*] within assessmentItem

Attributes:

- **outcomeIdentifier (required).** Data type = identifier.Type
- **showHide (required).** Data type = showHide.Type
- **identifier (required).** Data type = identifier.Type
- **title (optional).** Data type = string.Type

Elements:

- Members of flowStaticElementGroup
- PCDATA

4.147 <multiple>

Description: An expression that aggregates sub-expressions into a single unordered container.

Context:**See:**

- expression.ElementGroup

Elements:

- Members of expressionElementGroup

4.148 <not>

Description: An expression that performs boolean negation.

Context:**See:**

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.149 <null>

Description: A simple expression that returns the NULL value.

Context:**See:**

- expression.ElementGroup

4.150 <object>

Description: Defined by XHTML

Context:

- Occurs [1] within drawingInteraction
- Occurs [1] within gapImg
- Occurs [1] within members of graphicInteraction.ElementGroup
- Occurs [1] within positionObjectInteraction
- Occurs [1] within positionObjectStage

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type
- **data (required)**. Data type = string.Type
- **type (required)**. Data type = mimeType.Type
- **width (optional)**. Data type = length.Type
- **height (optional)**. Data type = length.Type

Elements:

- Members of objectFlow.ElementGroup
- PCDATA

4.151 <objectElements>

Description: Profile flag for the XHTML object element.

Context:

- Occurs [1] within contentProfile

4.152 objectFlow.ElementGroup

Description: The group of elements that can appear within <object>.

Group members: <a>, <abbr>, <acronym>, <address>, <associateInteraction>, , <big>, <blockquote>,
, <choiceInteraction>, <cite>, <code>, <customInteraction>, <dfn>, <div>, <dl>, <drawingInteraction>, , <endAttemptInteraction>, <extendedTextInteraction>, <feedbackBlock>, <feedbackInline>, <gapMatchInteraction>, <graphicAssociateInteraction>, <graphicGapMatchInteraction>, <graphicOrderInteraction>, <h1>, <h2>, <h3>, <h4>, <h5>, <h6>, <hotspotInteraction>, <hottext>, <hottextInteraction>, <hr>, <i>, , <inlineChoiceInteraction>, <kbd>, <m:math>, <matchInteraction>, <object>, , <orderInteraction>, <p>, <param>, <pre>, <printedVariable>, <q>, <rubricBlock>, <samp>, <selectPointInteraction>, <sliderInteraction>, <small>, , , <sub>, <sup>, <table>, <templateBlock>, <templateInline>, <textEntryInteraction>, <tt>, , <uploadInteraction>, <var>

Context:

- Occurs [*] within object

4.153 <objectType>

Description: Profile element for identifying a specific object mime-type.

Context:

- Occurs [*] within contentProfile

4.154

Description: Defined by XHTML

Context:**See:**

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- id (optional).** Data type = identifier.Type
- class (optional).** Data type = list of styleclass.Type
- xml:lang (optional).**
- label (optional).** Data type = string256.Type

Elements:

-

4.155 <or>

Description: An expression that performs a boolean or.

Context:

See:

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.156 <orderInteraction>

Description: Interaction in which candidates must (re-)order a set of choices

Context:

See:

- block.ElementGroup
- flow.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **responseIdentifier (required).** Data type = identifier.Type
- **shuffle (required).** Data type = boolean.Type
- **orientation (optional).** Data type = orientation.Type

Elements:

- <prompt>
- <simpleChoice>

4.157 <ordered>

Description: An expression that aggregates sub-expressions into a single ordered container.

Context:

See:

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.158 <ordinaryStatistic>

Description: An ordinary single-valued item statistic.

Context:**See:**

- itemStatistic.ElementGroup

Attributes:

- **name (required)**. Data type = identifier.Type
- **glossary (optional)**. Data type = uri.Type
- **context (required)**. Data type = uri.Type
- **caseCount (optional)**. Data type = integer.Type
- **stdError (optional)**. Data type = float.Type
- **stdDeviation (optional)**. Data type = float.Type
- **lastUpdated (optional)**. Data type = date.Type

Elements:

- <targetObject>
- <value>

4.159 orientation.Type

One of the following symbolic values:

- horizontal
- vertical

4.160 <outcomeDeclaration>

Description: Declares an outcome variable.

Context:

- Occurs [*] within assessmentItem

Attributes:

- **identifier (required)**. Data type = identifier.Type
- **cardinality (required)**. Data type = cardinality.Type
- **baseType (optional)**. Data type = baseType.Type
- **interpretation (optional)**. Data type = string.Type
- **longInterpretation (optional)**. Data type = uri.Type
- **normalMaximum (optional)**. Data type = float.Type

Elements:

- <defaultValue>

4.161 <p>

Description: Defined by XHTML

Context:**See:**

- block.ElementGroup

- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.162 <param>

Description: Defined by XHTML

Context:**See:**

- objectFlow.ElementGroup

Attributes:

- **name (required)**. Data type = string.Type
- **value (required)**. Data type = string.Type
- **valuetype (required)**. Data type = paramType.Type
- **type (optional)**. Data type = mimeType.Type

4.163 paramType.Type

One of the following symbolic values:

- DATA
- REF

4.164 <patternMatch>

Description: An expression for testing two string values using regular expressions.

Context:**See:**

- expression.ElementGroup

Attributes:

- **pattern (required)**. Data type = string.Type

Elements:

- Members of expression.ElementGroup

4.165 <positionObjectInteraction>

Description: Interaction in which the candidate must position objects over an existing image.

Context:

- Occurs [1..*] within positionObjectStage

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **responseIdentifier (required).** Data type = identifier.Type
- **centerPoint (optional).** Data type = list of integer.Type
- **maxChoices (required).** Data type = integer.Type

Elements:

- <object>

4.166 <positionObjectStage>

Description: Defines the background image to be used for positioning object tasks.

Context:

See:

- block.ElementGroup

Elements:

- <object>
- <positionObjectInteraction>

4.167 <power>

Description: An expression for raising one number to the power of another.

Context:

See:

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.168 <pre>

Description: Defined by XHTML

Context:

See:

- block.ElementGroup

- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.169 <presentationElements>

Description: Profile flag for the XHTML presentation elements.

Context:

- Occurs [1] within contentProfile

4.170 <printedVariable>

Description: An element used to insert the value of an item variable into the item body.

Context:**See:**

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type
- **identifier (required)**. Data type = identifier.Type
- **format (optional)**. Data type = string256.Type
- **base (optional)**. Data type = integer.Type

4.171 <printedVariables>

Description: Profile flag for the printedVariable feature.

Context:

- Occurs [1] within contentProfile

4.172 <product>

Description: An expression for calculating the product of a group of numbers.

Context:

See:

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.173 <prompt>

Description: An optional prompt for an interaction.

Context:

- Occurs [0..1] within members of blockInteraction.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inlineStatic.ElementGroup
- PCDATA

4.174 <q>

Description: Defined by XHTML

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **cite (optional).** Data type = uri.Type

Elements:

- Members of inline.ElementGroup

- PCDATA

4.175 <qtiMetadata>

Description: The root element for QTI-specific meta-data. Typically used within a manifest file in an IMS content package.

Context:

Can be the root element of an XML document.

Elements:

- <itemTemplate>
- <timeDependent>
- <composite>
- <interactionType>
- <feedbackType>
- <solutionAvailable>
- <toolName>
- <toolVersion>
- <toolVendor>

4.176 <random>

Description: An expression that extracts a random value from a container.

Context:

See:

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.177 <randomFloat>

Description: An expression that returns a random float from the specified range.

Context:

See:

- expression.ElementGroup

Attributes:

- **min (required).** Data type = float.Type
- **max (required).** Data type = float.Type

4.178 <randomInteger>

Description: An expression that returns a random integer from the specified range.

Context:

See:

- expression.ElementGroup

Attributes:

- **min (required)**. Data type = integer.Type
- **max (required)**. Data type = integer.Type
- **step (optional)**. Data type = integer.Type

4.179 <regexp>

Description: Profile flag for the regular-expression feature.

Context:

- Occurs [1] within contentProfile

4.180 <responseCondition>

Description: A response rule that contains groups of sub-rules which are followed conditionally based on the value of one or more expressions.

Context:**See:**

- responseRule.ElementGroup

Elements:

- <responseIf>
- <responseElseIf>
- <responseElse>

4.181 <responseDeclaration>

Description: Declares a response variable.

Context:

- Occurs [*] within assessmentItem

Attributes:

- **identifier (required)**. Data type = identifier.Type
- **cardinality (required)**. Data type = cardinality.Type
- **baseType (optional)**. Data type = baseType.Type

Elements:

- <defaultValue>
- <correctResponse>
- <mapping>
- <areaMapping>

4.182 <responseElse>

Description: A final group of rules to be followed unconditionally if all previous groups have been skipped for the containing response condition.

Context:

- Occurs [0..1] within responseCondition

Elements:

- Members of responseRule.ElementGroup

4.183 <responseElseIf>

Description: A conditional group of rules to be considered if all previous groups have been skipped for the containing response condition.

Context:

- Occurs [*] within responseCondition

Elements:

- Members of expression.ElementGroup
- Members of responseRule.ElementGroup

4.184 <responseIf>

Description: The first part of a response condition.

Context:

- Occurs [1] within responseCondition

Elements:

- Members of expression.ElementGroup
- Members of responseRule.ElementGroup

4.185 <responseProcessing>

Description: Defines the rules used to process the candidate's responses.

Context:

- Occurs [0..1] within assessmentItem

Can be the root element of an XML document.

Attributes:

- **template (optional).** Data type = uri.Type
- **templateLocation (optional).** Data type = uri.Type

Elements:

- Members of responseRule.ElementGroup

4.186 responseRule.ElementGroup

Description: A group of elements that define rules to be followed during response processing.

Group members: <exitResponse>, <responseCondition>, <setOutcomeValue>

Context:

- Occurs [*] within responseElse
- Occurs [*] within responseElseIf
- Occurs [*] within responseIf
- Occurs [*] within responseProcessing

4.187 <responseRules>

Description: Profile flag for the general response processing feature.

Context:

- Occurs [1] within contentProfile

4.188 <round>

Description: An expression for rounding a real number to an integer.

Context:

See:

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.189 <rounding>

Context:

- Occurs [1] within contentProfile

4.190 roundingMode.Type

One of the following symbolic values:

- decimalPlaces
- significantFigures

4.191 <rpTemplate>

Description: Profile element for identifying a specific response processing template.

Context:

- Occurs [*] within contentProfile

4.192 <rubric>

Description: Profile flag for the rubric feature.

Context:

- Occurs [1] within contentProfile

4.193 <rubricBlock>

Description: A structural part of the item body whose visibility depends on the role of the person viewing the item, typically containing instructions to a specific actor.

Context:

See:

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **view (required).** Data type = list of view.Type

Elements:

- Members of block.ElementGroup

4.194 <samp>

Description: Defined by XHTML

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.195 <selectPointInteraction>

Description: Interaction in which the candidate selects one or more points on an image.

Context:

See:

- block.ElementGroup
- flow.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type
- **responseIdentifier (required)**. Data type = identifier.Type
- **maxChoices (required)**. Data type = integer.Type

Elements:

- <prompt>
- <object>

4.196 <setCorrectResponse>

Description: A template rule that sets the correct value of a response variable.

Context:

See:

- templateRule.ElementGroup

Attributes:

- **identifier (required)**. Data type = identifier.Type

Elements:

- Members of expression.ElementGroup

4.197 <setDefaultValue>

Description: A template rule that sets the default value of an item variable.

Context:

See:

- templateRule.ElementGroup

Attributes:

- **identifier (required).** Data type = identifier.Type

Elements:

- Members of expression.ElementGroup

4.198 <setOutcomeValue>

Description: A response rule that sets the value of an outcome variable.

Context:**See:**

- responseRule.ElementGroup

Attributes:

- **identifier (required).** Data type = identifier.Type

Elements:

- Members of expression.ElementGroup

4.199 <setTemplateValue>

Description: A template rule that sets the value of a template variable.

Context:**See:**

- templateRule.ElementGroup

Attributes:

- **identifier (required).** Data type = identifier.Type

Elements:

- Members of expression.ElementGroup

4.200 shape.Type

One of the following symbolic values:

- circle
- default
- ellipse
- poly
- rect

4.201 showHide.Type

One of the following symbolic values:

- hide
- show

4.202 sign.Type

A trivial restriction of xsd:string.

4.203 <simpleAssociableChoice>

Description: The element used to describe the choices in simple association or matching tasks.

Context:

- Occurs [1..*] within associateInteraction
- Occurs [*] within simpleMatchSet

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **identifier (required).** Data type = identifier.Type
- **fixed (optional).** Data type = boolean.Type
- **matchGroup (optional).** Data type = list of identifier.Type
- **matchMax (required).** Data type = integer.Type

Elements:

- Members of flowStatic.ElementGroup
- PCDATA

4.204 simpleBlock.ElementGroup

Description: A group of elements that provide simple aggregating structure to the item body.

Group members: <blockquote>, <feedbackBlock>, <rubricBlock>

Context:

See:

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

4.205 <simpleChoice>

Description: The element used to describe the choices in simple selection or ordering tasks.

Context:

- Occurs [1..*] within choiceInteraction
- Occurs [1..*] within orderInteraction

Attributes:

- **id (optional).** Data type = identifier.Type

- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **identifier (required).** Data type = identifier.Type
- **fixed (optional).** Data type = boolean.Type

Elements:

- Members of flowStatic.ElementGroup
- PCDATA

4.206 simpleInline.ElementGroup

Description: A group of elements that both behave as and contain things that behave like spans of text.

Group members: <a>, <abbr>, <acronym>, , <big>, <cite>, <code>, <dfn>, , <feedbackInline>, <i>, <kbd>, <q>, <samp>, <small>, , , <sub>, <sup>, <tt>, <var>

Context:**See:**

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

4.207 <simpleMatchSet>

Description: Describes a set of choices for use in a matching task.

Context:

- Occurs [2] within matchInteraction

Elements:

- <simpleAssociableChoice>

4.208 <sliderInteraction>

Description: Interaction in which the candidate uses a slider to enter a constrained numeric response.

Context:**See:**

- block.ElementGroup
- flow.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**

- **label (optional)**. Data type = string256.Type
- **responseIdentifier (required)**. Data type = identifier.Type
- **lowerBound (required)**. Data type = float.Type
- **upperBound (required)**. Data type = float.Type
- **step (optional)**. Data type = integer.Type
- **stepLabel (optional)**. Data type = boolean.Type
- **orientation (optional)**. Data type = orientation.Type
- **reverse (optional)**. Data type = boolean.Type

Elements:

- <prompt>

4.209 <small>

Description: Defined by XHTML

Context:**See:**

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.210 <solutionAvailable>

Description: A meta-data flag indicating that the item contains a solution.

Context:

- Occurs [0..1] within qtiMetadata

4.211

Description: Defined by XHTML

Context:**See:**

- flow.ElementGroup

- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.212 string.Type

A trivial restriction of xsd:string.

4.213 string256.Type

A trivial restriction of xsd:string.

4.214 stringInteraction.ElementGroup

Description: A group of interactions that allow text-based responses to be entered by the user.

Group members: <extendedTextInteraction>, <textEntryInteraction>

Context:

Not applicable.

4.215 <stringMatch>

Description: An expression for testing two string values.

Context:**See:**

- expression.ElementGroup

Attributes:

- **caseSensitive (required)**. Data type = boolean.Type
- **substring (required)**. Data type = boolean.Type

Elements:

- Members of expression.ElementGroup

4.216

Description: Defined by XHTML

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.217 styleclass.Type

A trivial restriction of xsd:string.

4.218 <stylesheet>

Description: Associates a stylesheet with an item.

Context:

- Occurs [0..*] within assessmentItem

Attributes:

- **href (required).** Data type = uri.Type
- **type (required).** Data type = mimeType.Type
- **media (optional).** Data type = string.Type
- **title (optional).** Data type = string.Type

4.219 <sub>

Description: Defined by XHTML

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup

- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.220 <substring>

Description: An expression that tests a string to determine if it contains another.

Context:**See:**

- expression.ElementGroup

Attributes:

- **caseSensitive (required)**. Data type = boolean.Type

Elements:

- Members of expression.ElementGroup

4.221 <subtract>

Description: An expression for subtracting one number from another.

Context:**See:**

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.222 <sum>

Description: An expression for calculating the sum of a group of numbers.

Context:**See:**

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.223 <sup>

Description: Defined by XHTML

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.224 <table>

Description: Defined by XHTML

Context:

See:

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **summary (optional).** Data type = string.Type

Elements:

- <caption>
- <col>
- <colgroup>
- <thead>
- <tfoot>
- <tbody>

4.225 tableCell.ElementGroup

Description: Elements that can appear within a row of a table.

Group members: <td>, <th>

Context:

- Occurs [1..*] within tr

4.226 tableCellScope.Type

One of the following symbolic values:

- col
- colgroup
- row
- rowgroup

4.227 <tableElements>

Description: Profile flag for the XHTML table element.

Context:

- Occurs [1] within contentProfile

4.228 <targetObject>

Description: A reference to the object, such as an assessment item, or a sub-part of the object, to which an item statistic relates.

Context:

- Occurs [1..*] within members of itemStatistic.ElementGroup

Attributes:

- **identifier (required).** Data type = string.Type
- **partIdentifier (optional).** Data type = identifier.Type

4.229 <tbody>

Description: Defined by XHTML

Context:

- Occurs [1..*] within table

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- <tr>

4.230 <td>

Description: Defined by XHTML

Context:

See:

- tableCell.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type
- **headers (optional)**. Data type = list of identifier.Type
- **scope (optional)**. Data type = tableCellScope.Type
- **abbr (optional)**. Data type = string.Type
- **axis (optional)**. Data type = string.Type
- **rowspan (optional)**. Data type = integer.Type
- **colspan (optional)**. Data type = integer.Type

Elements:

- Members of flow.ElementGroup
- PCDATA

4.231 <templateBlock>

Description: A structural part of the item body whose visibility is conditionally controlled by a template variable.

Context:

See:

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type
- **templateIdentifier (required)**. Data type = identifier.Type
- **showHide (required)**. Data type = showHide.Type
- **identifier (required)**. Data type = identifier.Type

Elements:

- Members of blockStatic.ElementGroup

4.232 <templateCondition>

Description: A template rule that contains groups of sub-rules which are followed conditionally based on the value of one or more expressions.

Context:

See:

- templateRule.ElementGroup

Elements:

- <templateIf>
- <templateElseIf>
- <templateElse>

4.233 <templateDeclaration>

Description: Declares a template variable.

Context:

- Occurs [*] within assessmentItem

Attributes:

- **identifier (required).** Data type = identifier.Type
- **cardinality (required).** Data type = cardinality.Type
- **baseType (optional).** Data type = baseType.Type
- **paramVariable (required).** Data type = boolean.Type
- **mathVariable (required).** Data type = boolean.Type

Elements:

- <defaultValue>

4.234 templateElement.ElementGroup

Description: Elements whose visibility is conditionally controlled by a template variable.

Group members: <templateBlock>, <templateInline>

Context:

Not applicable.

4.235 <templateElse>

Description: A final group of rules to be followed unconditionally if all previous groups have been skipped for the containing template condition.

Context:

- Occurs [0..1] within templateCondition

Elements:

- Members of templateRule.ElementGroup

4.236 <templateElseIf>

Description: A conditional group of rules to be considered if all previous groups have been skipped for the containing template condition.

Context:

- Occurs [*] within templateCondition

Elements:

- Members of expression.ElementGroup
- Members of templateRule.ElementGroup

4.237 <templateIf>

Description: The first part of a template condition.

Context:

- Occurs [1] within templateCondition

Elements:

- Members of *expression.ElementGroup*
- Members of templateRule.ElementGroup

4.238 <templateInline>

Description: A span of text (or equivalent) whose visibility is conditionally controlled by a template variable.

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **templateIdentifier (required).** Data type = identifier.Type
- **showHide (required).** Data type = showHide.Type
- **identifier (required).** Data type = identifier.Type

Elements:

- Members of inlineStatic.ElementGroup
- PCDATA

4.239 <templateProcessing>

Description: Defines the rules used for calculating the values of the template variables.

Context:

- Occurs [0..1] within assessmentItem

Elements:

- Members of templateRule.ElementGroup

4.240 templateRule.ElementGroup

Description: A group of elements that define rules to be followed during template processing.

Group members: <exitTemplate>, <setCorrectResponse>, <setDefaultValue>, <setTemplateValue>, <templateCondition>

Context:

- Occurs [*] within templateElse
- Occurs [*] within templateElseIf
- Occurs [*] within templateIf
- Occurs [1..*] within templateProcessing

4.241 <templates>

Description: Profile flag for the item template feature.

Context:

- Occurs [1] within contentProfile

4.242 <textElements>

Description: Profile flag for the XHTML text elements.

Context:

- Occurs [1] within contentProfile

4.243 <textEntryInteraction>

Description: Interaction that allows the candidate to supply a span of text to fill a gap.

Context:

See:

- flow.ElementGroup
- inline.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type

- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **responseIdentifier (required).** Data type = identifier.Type
- **base (optional).** Data type = integer.Type
- **stringIdentifier (optional).** Data type = identifier.Type
- **expectedLength (optional).** Data type = integer.Type
- **patternMask (optional).** Data type = string.Type
- **placeholderText (optional).** Data type = string.Type

4.244 <tfoot>

Context:

- Occurs [0..1] within table

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- <th>

4.245 <th>

Description: Defined by XHTML

Context:

- Occurs [1..*] within tfoot

See:

- tableCell.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **headers (optional).** Data type = list of identifier.Type
- **scope (optional).** Data type = tableCellScope.Type
- **abbr (optional).** Data type = string.Type
- **axis (optional).** Data type = string.Type
- **rowspan (optional).** Data type = integer.Type
- **colspan (optional).** Data type = integer.Type

Elements:

- Members of flow.ElementGroup
- PCDATA

4.246 <thead>

Context:

- Occurs [0..1] within table

Attributes:

- **id (optional)**. Data type = identifier.Type
- **class (optional)**. Data type = list of styleclass.Type
- **xml:lang (optional)**.
- **label (optional)**. Data type = string256.Type

Elements:

- <tr>

4.247 <timeDependent>

Description: Profile flag for the time-dependence feature.

Context:

- Occurs [1] within contentProfile
- Occurs [0..1] within qtiMetadata

4.248 toleranceMode.Type

One of the following symbolic values:

- absolute
- exact
- relative

4.249 <toolName>

Description: A meta-data element containing the name of the tool used to create the object.

Context:

- Occurs [0..1] within qtiMetadata

4.250 <toolVendor>

Description: A meta-data element containing the name of the company that produced the tool used to create the object.

Context:

- Occurs [0..1] within qtiMetadata

4.251 <toolVersion>

Description: A meta-data element containing the version of the tool used to create the object.

Context:

- Occurs [0..1] within qtiMetadata

4.252 <tr>

Description: Defined by XHTML

Context:

- Occurs [1..*] within tbody
- Occurs [1..*] within thead

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of tableCell.ElementGroup

4.253 <truncate>

Description: An expression for truncating a real number to an integer.

Context:

See:

- expression.ElementGroup

Elements:

- Members of expression.ElementGroup

4.254 <tt>

Description: Defined by XHTML

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.255

Description: Defined by XHTML

Context:

See:

- block.ElementGroup
- blockStatic.ElementGroup
- flow.ElementGroup
- flowStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

-

4.256 <uploadInteraction>

Description: Interaction in which the candidate uploads a file representing their response.

Context:

See:

- block.ElementGroup
- flow.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type
- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type
- **responseIdentifier (required).** Data type = identifier.Type
- **type (optional).** Data type = mimeType.Type

Elements:

- <prompt>

4.257 uri.Type

A trivial restriction of xsd:anyURI.

4.258 <usageData>

Description: The root element of a usage data XML document instance. Usage data are also referred to as item statistics.

Context:

Can be the root element of an XML document.

Attributes:

- **glossary (optional).** The default glossary in which the names of the itemStatistics are defined. Data type = uri.Type

Elements:

- Members of itemStatistic.ElementGroup

4.259 <usageDataVocabulary>

Description: Profile flag for usage-data files.

Context:

- Occurs [*] within bankProfile

4.260 <value>

Description: A single data value from one of the base-types.

Context:

- Occurs [1..*] within correctResponse
- Occurs [1..*] within defaultValue
- Occurs [1] within ordinaryStatistic

Attributes:

- **fieldIdentifier (optional).** Data type = identifier.Type
- **baseType (optional).** Data type = baseType.Type

4.261 <var>

Description: Defined by XHTML

Context:

See:

- flow.ElementGroup
- flowStatic.ElementGroup
- inline.ElementGroup
- inlineStatic.ElementGroup
- objectFlow.ElementGroup

Attributes:

- **id (optional).** Data type = identifier.Type
- **class (optional).** Data type = list of styleclass.Type

- **xml:lang (optional).**
- **label (optional).** Data type = string256.Type

Elements:

- Members of inline.ElementGroup
- PCDATA

4.262 <variable>

Description: A simple expression returning the value of an item variable

Context:**See:**

- expression.ElementGroup

Attributes:

- **identifier (required).** Data type = identifier.Type

4.263 variableDeclaration.ElementGroup

Group members: <outcomeDeclaration>, <responseDeclaration>, <templateDeclaration>

Context:

Not applicable.

4.264 view.Type

One of the following symbolic values:

- author
- candidate
- proctor
- scorer
- tutor

About This Document

Title	IMS Question and Test Interoperability XML Binding
Editor	Steve Lay (University of Cambridge)
Version	2.0
Version Date	24 January 2005
Status	Final Specification
Summary	This document describes the QTI XML Binding specification.
Revision Information	24 January 2005
Purpose	This document has been approved by the IMS Technical Board and is made available for adoption.
Document Location	http://www.imsglobal.org/question/qti_v2p0/imsqti_bindv2p0.html

To register any comments or questions about this specification please visit:
<http://www.imsglobal.org/developers/ims/imsforum/categories.cfm?catid=23>

List of Contributors

The following individuals contributed to the development of this document:

Name	Organization	Name	Organization
Niall Barr	CETIS	Joshua Marks	McGraw-Hill
Sam Easterby-Smith	Canvas Learning	David Poor	McGraw-Hill
Jeanne Ferrante	ETS	Greg Quirus	ETS
Pierre Gorissen	SURF	Niall Sclater	CETIS
Regina Hoag	ETS	Colin Smythe	IMS
Christian Kaefer	McGraw-Hill	GT Springer	Texas Instruments
John Kleeman	Question Mark	Colin Tattersall	OUNL
Steve Lay	UCLES	Rowin Young	CETIS
Jez Lord	Canvas Learning		

Revision History

Version No.	Release Date	Comments
Base Document 2.0	09 March 2004	The first version of the QTI Item v2.0 specification.
Public Draft 2.0	07 June 2004	The Public Draft version 2.0 of the QTI Item XML Binding.
Final 2.0	24 January 2005	The Final version 2.0 of the QTI specification.

Index

A

abstract class/element Group

associableChoice 14

atomicBlock 15, 47

atomicInline 16

block 12, 15, 18, 19, 21, 25, 27, 28, 32, 33, 37, 38, 39, 40, 41, 42, 43, 44, 45, 51, 54, 58, 59, 60, 62, 64, 69, 70, 72, 73, 78, 80, 87

blockInteraction 18, 64

blockStatic 12, 15, 18, 19, 27, 28, 33, 37, 40, 41, 42, 44, 45, 58, 61, 63, 69, 72, 78, 80, 87

bodyElement 19

choice 9, 21

dlElement 25, 28, 29

expression 13, 17, 23, 24, 25, 26, 27, 29, 30, 31, 35, 39, 40, 47, 49, 50, 51, 53, 54, 55, 56, 57, 59, 61, 62, 64, 65, 66, 67, 68, 70, 71, 75, 77, 82, 86, 89

feedbackElement 33

flow 11, 12, 15, 16, 17, 18, 19, 21, 22, 25, 26, 27, 28, 30, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 48, 52, 55, 57, 58, 59, 61, 63, 64, 69, 70, 72, 73, 74, 76, 78, 80, 82, 83, 84, 86, 87, 88

flowStatic 11, 12, 15, 16, 17, 19, 21, 22, 27, 28, 30, 33, 34, 36, 40, 41, 42, 44, 45, 46, 52, 56, 57, 58, 61, 63, 64, 69, 72, 73, 74, 75, 76, 78, 80, 82, 86, 87, 88

gapChoice 36, 37

graphicInteraction 39, 57

hotspot 43

inline 11, 12, 16, 17, 19, 20, 21, 22, 27, 29, 30, 34, 36, 40, 41, 42, 44, 45, 46, 47, 48, 52, 57, 61, 63, 64, 69, 70, 73, 74, 75, 76, 77, 78, 82, 83, 86, 88, 89

inlineInteraction 48

inlineStatic 11, 12, 16, 17, 19, 21, 22, 27, 30, 34, 36, 44, 45, 46, 48, 52, 57, 63, 64, 69, 73, 74, 75, 76, 78, 82, 86, 88

interaction 24, 30, 37, 48, 50, 64

itemStatistic 20, 51, 60, 79, 88

objectFlow 11, 12, 15, 16, 17, 18, 19, 21, 22, 25, 27, 28, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 48, 52, 55, 57, 58, 59, 61, 63, 64, 69, 70, 72, 73, 74, 75, 76, 77, 78, 80, 82, 83, 86, 87, 88

responseRule 31, 66, 67, 68, 71

simpleBlock 18, 72

simpleInline 47, 73

stringInteraction 75

tableCell 35, 79, 80, 84, 86

templateElement 81

templateRule 31, 70, 71, 81, 82, 83

variableDeclaration 26, 89

actor

author 89

candidate 15, 21, 28, 32, 37, 38, 39, 43, 44, 50, 51, 54, 56, 62, 67, 70, 73, 83, 87, 89

proctor 89

scorer 89

tutor 89

adaptive 12, 14, 23, 35

aggregation/element

composite 23, 65

feedbackIntegrated 24, 34

feedbackModal 24, 34

hypertextElement 24, 45

imageElement 24, 46

imageType 24, 46

imsmd 46, 56

imsqtimd 47, 56

itemTemplate 51, 65

listElements 23, 52

lomMetadata 53, 56

mathElement 24, 55

objectElements 23, 57

objectType 23, 58

presentationElements 23, 63

printedVariables 24, 63

regexp 24, 66

responseRules 24, 68

rounding 24, 31, 68

rpTemplate 24, 68

rubric 24, 69

solutionAvailable 65, 74

tableElements 23, 79

templates 23, 83

textElements 23, 83

timeDependent 14, 23, 65, 85

toolName 14, 65, 85

toolVendor 65, 85

usageDataVocabulary 16, 88

Assessment 79

assessmentItem 14, 51, 56, 60, 66, 67, 76, 81, 83

attribute of assessmentItem

timeDependent 14, 23, 65, 85

toolName 14, 65, 85

attribute of itemStatistic

caseCount 20, 60

context 20, 60

lastUpdated 20, 60

stdDeviation 20, 60

stdError 20, 60

attribute of sliderInteraction

reverse 74

stepLabel 74

attribute of stringInteraction

expectedLength 33, 84

patternMask 33, 84

placeholderText 33, 84

stringIdentifier 33, 84

attribute of tableCell

axis 80, 84

colspan 80, 84

headers 80, 84

rowspan 80, 84

scope 80, 84

B

base 9, 17, 33, 49, 63, 84, 88

baseType 17, 60, 66, 81, 88

Binding 8, 10

C

candidate 15, 21, 28, 32, 37, 38, 39, 43, 44, 50, 51, 54, 56, 62, 67, 70, 73, 83, 87, 89

cardinality 20, 60, 66, 81

caseSensitive 75, 77

centerPoint 62

cite 19, 21, 35, 36, 47, 48, 58, 64, 73

class 11, 12, 15, 16, 17, 19, 20, 21, 22, 23, 25, 27, 28, 29, 30, 33, 34, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 51, 52, 55, 57, 58, 59, 61, 62, 63, 64,

69, 70, 72, 73, 74, 75, 76, 77, 78, 79, 80, 82, 83, 84, 85, 86, 87, 88	35, 47, 48, 50, 58	li 9, 19, 35, 52, 58, 87
class/element	equal 29, 30, 31, 32, 40, 53	lt 31, 32, 53
abbr 11, 19, 35, 36, 47, 48, 58, 73, 80, 84	equalRounded 31, 32	lte 31, 32, 53
acronym 12, 19, 35, 36, 47, 48, 58, 73	exitResponse 31, 68	mapEntry 53, 54
address 12, 15, 18, 19, 35, 36, 58	exitTemplate 31, 83	mapping 13, 20, 21, 53, 54, 66
anyN 13, 31	extendedTextInteraction 18, 19, 32, 35, 50, 58, 75	mapResponse 31, 53
areaMapEntry 13, 14	feedbackBlock 18, 19, 33, 35, 36, 58, 72	mapResponsePoint 31, 54
areaMapping 13, 66	feedbackInline 19, 33, 34, 35, 36, 47, 48, 58, 73	match 31, 32, 54
assessmentItem 14, 51, 56, 60, 66, 67, 76, 81, 83	fieldValue 31, 32, 35	matchInteraction 18, 19, 35, 50, 54, 58, 73
associableHotspot 14, 19, 21, 38, 39, 43	gap 14, 19, 21, 36, 37, 47, 48, 83	math 9, 18, 35, 36, 47, 48, 55, 58
associateInteraction 15, 18, 19, 35, 50, 58, 72	gapImg 14, 19, 21, 36, 39, 57	member 31, 32, 55
bankProfile 16, 56, 88	gapMatchInteraction 18, 19, 35, 36, 37, 50, 58	metadataProfile 16, 24, 46, 47, 53, 55
baseValue 17, 31	gapText 14, 19, 21, 36, 37	modalFeedback 14, 36, 56
big 17, 19, 35, 36, 47, 48, 58, 73	graphicAssociateInteraction 14, 18, 19, 35, 38, 39, 50, 58	multiple 20, 21, 31, 32, 56
blockquote 18, 19, 35, 36, 58, 72	graphicGapMatchInteraction 14, 18, 19, 35, 37, 38, 39, 50, 58	null 31, 57
br 16, 19, 35, 36, 47, 48, 58	graphicOrderInteraction 18, 19, 35, 39, 43, 50, 58	object 19, 29, 35, 36, 37, 38, 39, 44, 47, 48, 57, 58, 62, 70, 79, 85
caption 19, 20, 47, 78	gt 31, 32, 39	ol 18, 19, 35, 36, 52, 58
categorizedStatistic 20, 51, 54	gte 31, 32, 40	or 8, 9, 10, 16, 23, 24, 29, 31, 32, 34, 35, 36, 40, 50, 53, 55, 59, 66, 70, 72, 79, 81, 82
choiceInteraction 18, 19, 21, 35, 50, 58, 72	h1 15, 18, 19, 35, 36, 40, 58	ordered 20, 31, 32, 47, 59
code 19, 22, 35, 36, 47, 48, 58, 73	h2 15, 18, 19, 35, 36, 40, 58	orderInteraction 18, 19, 35, 50, 58, 59, 72
col 19, 22, 23, 78, 79	h3 15, 18, 19, 35, 36, 41, 58	ordinaryStatistic 51, 59, 88
colgroup 19, 22, 78, 79	h4 15, 18, 19, 35, 36, 41, 58	outcomeDeclaration 14, 60, 89
contains 23, 31, 55, 66, 74, 77, 81	h5 15, 18, 19, 35, 36, 42, 58	param 58, 61
contentProfile 12, 23, 34, 45, 46, 50, 52, 55, 56, 58, 63, 66, 68, 69, 79, 83, 85	h6 15, 18, 19, 35, 36, 42, 58	patternMatch 31, 32, 61
correct 24, 31, 66, 70, 88	hotspotChoice 19, 21, 39, 43, 44	positionObjectInteraction 19, 50, 57, 62
correctResponse 24, 66, 88	hotspotInteraction 18, 19, 35, 39, 43, 50, 58	positionObjectStage 18, 57, 62
customInteraction 18, 19, 24, 35, 50, 58	hottext 19, 21, 35, 36, 44, 47, 48, 58	power 31, 32, 62
customOperator 25, 31	hottextInteraction 18, 19, 35, 44, 50, 58	pre 15, 18, 19, 35, 36, 38, 43, 44, 58, 62
dd 19, 25, 28, 35	hr 11, 18, 19, 35, 36, 45, 58, 76	printedVariable 19, 35, 36, 47, 48, 58, 63
default 26, 31, 70, 71, 88	img 16, 19, 35, 36, 46, 47, 48, 58	product 31, 32, 64
delete 26, 31	index 31, 32, 47	prompt 15, 19, 21, 28, 33, 37, 38, 39, 44, 48, 55, 59, 64, 70, 74, 87
dfn 19, 26, 35, 36, 47, 48, 58, 73	inlineChoice 19, 21, 47, 48	qtiMetadata 23, 34, 50, 51, 65, 74, 85
div 18, 19, 27, 35, 36, 58	inlineChoiceInteraction 19, 35, 47, 48, 50, 58	random 31, 32, 65
divide 27, 31	inside 31, 32, 49	randomFloat 31, 65
dl 18, 19, 28, 35, 36, 58	integerDivide 31, 32, 49	randomInteger 31, 65
drawingInteraction 18, 19, 28, 35, 50, 57, 58	integerModulus 31, 32, 49	responseCondition 66, 67, 68
dt 19, 28, 29, 47	integerToFloat 31, 32, 49	responseDeclaration 13, 14, 24, 54, 66, 89
durationGTE 29, 31, 32	isNull 31, 32, 51	responseElse 66, 67, 68
durationLT 29, 31, 32	itemBody 14, 18, 19, 51	responseElseIf 32, 66, 67, 68
em 19, 29, 35, 36, 47, 48, 58, 73	kbd 19, 35, 36, 47, 48, 51, 58, 73	responseSelf 32, 66, 67, 68
endAttemptInteraction 19, 30,		

- responseProcessing 14, 67, 68
- round 31, 32, 68
- rubricBlock 18, 19, 35, 36, 58, 69, 72
- samp 19, 35, 36, 47, 48, 58, 69, 73
- selectPointInteraction 18, 19, 35, 39, 50, 58, 70
- setCorrectResponse 32, 70, 83
- setDefaultValue 32, 70, 83
- setOutcomeValue 32, 68, 71
- setTemplateValue 32, 71, 83
- simpleAssociableChoice 14, 15, 19, 21, 36, 72, 73
- simpleChoice 19, 21, 36, 59, 72
- simpleMatchSet 55, 72, 73
- sliderInteraction 18, 19, 35, 50, 58, 73
- small 19, 35, 36, 47, 48, 58, 73, 74
- span 19, 34, 35, 36, 47, 48, 58, 73, 74, 82, 83
- stringMatch 31, 32, 75
- strong 19, 35, 36, 47, 48, 58, 73, 76
- stylesheet 14, 76
- sub 13, 19, 35, 36, 47, 48, 56, 58, 59, 66, 73, 76, 79, 81
- subtract 31, 32, 77
- sum 31, 32, 77
- sup 19, 35, 36, 47, 48, 58, 73, 78
- table 18, 19, 20, 22, 23, 35, 36, 58, 78, 79, 84, 85
- targetObject 21, 60, 79
- tbody 19, 78, 79, 86
- td 19, 79, 80
- templateBlock 18, 19, 35, 36, 58, 80, 81
- templateCondition 81, 82, 83
- templateDeclaration 14, 81, 89
- templateElse 81, 83
- templateElseIf 32, 81, 82, 83
- templateIf 32, 81, 82, 83
- templateInline 19, 35, 36, 47, 48, 58, 81, 82
- templateProcessing 14, 83
- textEntryInteraction 19, 35, 47, 48, 50, 58, 75, 83
- tfoot 19, 78, 84
- th 19, 79, 84
- thead 19, 78, 85, 86
- tr 19, 79, 80, 85, 86
- truncate 31, 32, 86
- tt 19, 35, 36, 47, 48, 58, 73, 86
- ul 18, 19, 35, 36, 52, 58, 87
- uploadInteraction 18, 19, 35, 50, 58, 87
- usageData 51, 88
- var 19, 35, 36, 47, 48, 58, 73, 88
- variable 24, 26, 31, 53, 54, 56, 60, 63, 66, 70, 71, 80, 81, 82, 89
- Content Package 65
- coords 13, 15, 24, 43, 49
- D**
- data 8, 57, 88
- datatype
 - boolean 10, 13, 14, 15, 17, 19, 21, 36, 37, 38, 43, 44, 47, 48, 55, 56, 59, 72, 73, 74, 75, 77, 81
 - date 20, 25, 60
 - float 13, 14, 17, 20, 30, 35, 49, 53, 54, 60, 65, 74
 - integer 13, 15, 17, 20, 21, 31, 33, 37, 38, 43, 44, 47, 49, 55, 60, 62, 63, 65, 66, 68, 70, 72, 74, 80, 84, 86
 - language 52
 - length 46, 52, 57
 - contentType 11, 56, 57, 61, 76, 87
 - sign 72
 - string 14, 17, 24, 26, 30, 33, 37, 47, 52, 53, 56, 57, 60, 61, 72, 75, 76, 77, 78, 79, 80, 84
 - string256 11, 12, 14, 15, 16, 17, 19, 20, 21, 22, 23, 25, 26, 27, 28, 29, 30, 33, 34, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 51, 52, 55, 57, 58, 59, 61, 62, 63, 64, 69, 70, 72, 73, 74, 75, 76, 77, 78, 79, 80, 82, 84, 85, 86, 87, 89
 - styleclass 11, 12, 15, 16, 17, 19, 20, 21, 22, 23, 25, 27, 28, 29, 30, 33, 34, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 51, 52, 55, 57, 58, 59, 61, 62, 63, 64, 69, 70, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89
 - uri 11, 17, 19, 20, 25, 46, 60, 64, 67, 76, 87, 88
- defaultValue 14, 26, 54, 60, 66, 81, 88
- definition 25
- duration 17
- E**
- enumeration
 - cardinality 20, 60, 66, 81
 - feedbackType 34, 35, 65
 - interactionType 24, 50, 65
 - paramType 61
 - tableCellScope 79, 80, 84
- expectedLines 33
- F**
- fieldIdentifier 35, 88
- figures 31
- fixed 15, 36, 37, 38, 43, 44, 47, 72, 73
- format 63
- G**
- glossary 20, 60, 88
- H**
- height 46, 57
- hotspotLabel 15, 43
- href 11, 76
- I**
- id 11, 12, 15, 16, 17, 19, 20, 21, 22, 23, 25, 27, 28, 29, 30, 33, 34, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 51, 52, 55, 57, 58, 59, 61, 62, 63, 64, 69, 70, 72, 73, 74, 75, 76, 77, 78, 79, 80, 82, 83, 84, 85, 86, 87, 88
- identifier 11, 12, 14, 15, 16, 17, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 51, 52, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 66, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89
- IMS Specifications
 - Question and Test Interoperability 8, 9, 10, 14, 23, 24, 47, 65
 - interpretation 24, 26, 60
- Item 16, 18, 19, 26, 33, 50, 51, 59, 63, 69, 70, 72, 74, 76, 79, 80, 83, 88, 89

L label 11, 12, 14, 15, 16, 17, 19, 20, 21, 22, 23, 25, 26, 27, 28, 29, 30, 33, 34, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 51, 52, 55, 57, 58, 59, 61, 62, 63, 64, 69, 70, 72, 73, 74, 75, 76, 77, 78, 79, 80, 82, 84, 85, 86, 87, 89 lang 11, 12, 14, 15, 16, 17, 19, 20, 21, 22, 23, 25, 26, 27, 28, 29, 30, 33, 34, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 51, 52, 55, 57, 58, 59, 61, 62, 63, 64, 69, 70, 72, 73, 74, 75, 76, 77, 78, 79, 80, 82, 84, 85, 86, 87, 89 LOM 53 longdesc 46 longInterpretation 60 lowerBound 13, 54, 74 M mapKey 53 mappedValue 13, 53 matchGroup 15, 36, 37, 38, 72 matchMax 15, 37, 38, 72 mathVariable 24, 55, 81 max 13, 65, 66 maxAssociations 15, 38, 55 maxChoices 21, 43, 44, 62, 70 maxStrings 33 media 76 Meta-data 46, 47, 51, 53, 55, 65, 74, 85 min 13, 65, 66 N name 20, 60, 61, 85	Namespace 8, 25 normalMaximum 60 O objectLabel 37 orientation 59, 60, 74 outcomeIdentifier 33, 34, 56 Outcomes 33, 34 P paramVariable 81 partIdentifier 79 pattern 61 proctor 89 R Response 21, 24, 31, 32, 50, 53, 54, 56, 66, 67, 68, 70, 71, 73, 87 responseIdentifier 15, 21, 25, 28, 30, 33, 37, 38, 39, 43, 44, 48, 55, 59, 62, 70, 74, 84, 87 responseProcessing 14, 67, 68 roundingMode 31, 68 S Schema 8, 9, 10 scorer 89 shape 13, 15, 43, 49, 71 showHide 33, 34, 56, 71, 80, 82 shuffle 15, 21, 37, 48, 55, 59 src 46 step 66, 74 Structure 15, 18, 19, 35, 36, 72 substring 31, 32, 75, 77 summary 78 T template 31, 51, 67, 68, 70, 71, 80, 81, 82, 83	templateIdentifier 80, 82 templateLocation 67 templateProcessing 14, 83 title 14, 30, 56, 76 tolerance 30 toleranceMode 30, 85 toolVersion 14, 65, 85 tutor 89 type 8, 10, 11, 12, 13, 14, 15, 16, 17, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89 U upperBound 14, 54, 74 V value 17, 24, 26, 34, 35, 47, 49, 50, 51, 53, 54, 55, 56, 57, 60, 61, 63, 65, 66, 70, 71, 81, 88, 89 valuetype 61 view 69, 89 Vocabulary 10 W width 46, 57 X XML 8, 10, 11, 14, 16, 23, 65, 67, 88 XSD 8, 9, 10
---	--	---

IMS Global Learning Consortium, Inc. ("IMS/GLC") is publishing the information contained in this IMS Question and Test Interoperability XML Binding ("Specification") for purposes of scientific, experimental, and scholarly collaboration only.

IMS/GLC makes no warranty or representation regarding the accuracy or completeness of the Specification.

This material is provided on an "As Is" and "As Available" basis.

The Specification is at all times subject to change and revision without notice.

It is your sole responsibility to evaluate the usefulness, accuracy, and completeness of the Specification as it relates to you.

IMS/GLC would appreciate receiving your comments and suggestions.

Please contact IMS/GLC through our website at <http://www.imsglobal.org>

Please refer to Document Name: IMS Question and Test Interoperability XML Binding

Date: 24 January 2005

